

ABBEYTILE Product Specification

TECHNICAL SPECIFICATION

Construction:	Multi-height loop pile
Colour:	Ohio
Face Yarn:	100% Solution Dyed Nylon
Dye Method:	Dye injection/space dyed
Total Pile Mass:	750 g/m ² (22oz)
Finished Pile Height:	4mm average
Backing:	Cushion Back
Total Thickness:	10mm average
Module Size:	500mm x 500mm
Box Quantity:	5.0m ² (20 tiles per box)

PERFORMANCE SPECIFICATION

Flammability:	Radiant Panel Test AS/ISO 9239-1 CRF = 7.7kw/m ² Smoke = 148 %mins NCC compliant in all building classifications
Dimensional Stability:	LESS than 0.2% at both Primary and Secondary backing levels
Colourfastness:	Meets or exceeds the relevant Australian Standard in the following tests: To light Xenon Arc Test: (5-6) To Shampoo AS2111.19.2: (3-4) To Rubbing AS 2111.19.1: (4) (Wet and Dry)
Castor Chair Test:	(BS.EN985) Pass = A (3.9)
VOC Emissions:	0.185mg/m ² /hour when tested to ASTM D5116-2010

WARRANTIES

CTA Group provides the following warranties for all ABBEYTILE products.

- 15 year wear warranty.
- 15 year dimensional stability.
- Lifetime design availability.

INSTALLATION

Grid-stick method using low-VOC water based acrylic adhesive as per AS 2455 Parts 1 & 2.

Full stick recommended for rolling load areas.

Quarter turn installation is recommended for tiles with complex design patterns.

ENVIRONMENTAL

1. ABBEYTILE has been independently certified as low-VOC emitting and gains 2 points in the IEQ-11 section of the Green Star - Office Interiors rating tool.
2. At end of product life CTA Group provides the highest possible level of product stewardship by offering a product reuse and renewal option.

Date of issue: 15th January 2016

- Specifications are subject to normal manufacturing tolerances and may be altered without notice to improve this product.
- Product may vary from dye lot to dye lot.

CALL CTA ON 1300 282 282
TO ARRANGE A MEETING WITH A SALES CONSULTANT
VICTORIA | NEW SOUTH WALES | QUEENSLAND | WESTERN AUSTRALIA

CTA
WWW.CTAGROUP.COM.AU